

Certificate of Appropriateness

Milwaukee Historic Preservation Commission/841 N Broadway/Milwaukee, WI 53202/phone 414-286-5712

Property

Description of work

Belleview Terrace Condominiums: 2579, 2581, 2587, & 2591 N Terrace Avenue. North Point North

Per condominium board agreement in this file, all units are approved to replace their windows with the following Marvin aluminum clad product until 12/31/2028. A one inch variance on measurements is allowed per window, to allow for construction variances, and building shifting and settling. Each unit must apply individually at the time of the project, but will receive an expedited staff approval per this agreement.

- 5 3-pane casement windows 52 X 74 inches
- 2 4-pane casement windows 52 X 100 inches
- 2 2-pane casement windows 52 X 50 inches

Date issued

6/26/23

In accordance with the provisions of Section 320-21 (11) and (12) of the Milwaukee Code of Ordinances, the Milwaukee Historic Preservation Commission has issued a certificate of appropriateness for the work listed above. The work was found to be consistent with preservation guidelines as aluminum windows are compatible with this era of building. The following conditions apply to this certificate of appropriateness:

N/A

All work must be done in a craftsman-like manner, and must be completed prior to 12/31/2028. Staff must approve any changes or additions to this certificate before work begins. Work that is not completed in accordance with this certificate may be subject to correction orders or citations. If you require technical assistance, please contact Historic Preservation staff as follows: Phone: (414) 286-5712 E-mail: hpc@milwaukee.gov.

If permits are required, you are responsible for obtaining them from the Milwaukee Development Center. If you have questions about permit requirements, please consult the Development Center's web site, www.milwaukee.gov/lms, or call (414) 286-8210.


City of Milwaukee Historic Preservation

m auss

The following is a schedule of the windows and doors for this project. For additional unit details, please see Line Item Quotes. Additional charges, tax or Terms and Conditions may apply. Detail pricing is per unit.

Line #1	Mark Unit:	Net Price:		
		Ext. Net Price:	USD	





Entered As: RO MO 49 1/2" X 51 3/4" FS 49" X 51 1/2" RO 50" X 52" Cashmere Clad Exterior Primed Pine Interior 2W1H - Rectangle Assembly Assembly Rough Opening 50" X 52"

Unit: A1 Ultimate Casement - Left Hand Basic Frame 24 1/2" X 51 1/2" Rough Opening 25 1/2" X 52" Cashmere Clad Sash Exterior Primed Pine Sash Interior IG - 3/4" - 1 Lite Low E2 w/Argon Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Satin Taupe Folding Handle Satin Taupe Multi - Point Lock Aluminum Screen Satin Taupe Surround Bright View Mesh

Ultimate Casement - Right Hand Basic Frame 24 1/2" X 51 1/2" Rough Opening 25 1/2" X 52" Cashmere Clad Sash Exterior Primed Pine Sash Interior IG - 3/4" - 1 Lite Low E2 w/Argon Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Satin Taupe Folding Handle Satin Taupe Multi - Point Lock Aluminum Screen Satin Taupe Surround **Bright View Mesh** Standard Mull Charge 5 1/4" Jambs Nailing Fin

***Note: This configuration meets a minimum structural performance of DP 20 through either physical testing or calculations in accordance with AAMA 450 and building code requirements. Mull certification ratings may vary from individual unit certification ratings. Reference the mulling chapter of the ADM for additional information.


***Note: Unit Availability and Price is Subject to Change

Line #2	Mark Unit:	Net Price:		
Qty: 1		Ext. Net Price:	USD	



Cashmere Clad Exterior Primed Pine Interior 3W1H - Rectangle Assembly Assembly Rough Opening 74" X 52"

Unit: A1 Ultimate Casement - Left Hand Basic Frame 24 21/64" X 51 1/2" Rough Opening 25 21/64" X 52"



As Viewed From The Exterior

Entered As: RO MO 73 1/2" X 51 3/4" FS 73" X 51 1/2" RO 74" X 52" Cashmere Clad Sash Exterior
Primed Pine Sash Interior
IG - 3/4" - 1 Lite
Low E2 w/Argon
Black Perimeter Bar
Ogee Interior Glazing Profile
Standard Bottom Rail
Beige Weather Strip
Satin Taupe Folding Handle
Satin Taupe Multi - Point Lock
Aluminum Screen
Satin Taupe Surround
Bright View Mesh

Unit: A2

Ultimate Casement - Stationary
Basic Frame 24 21/64" X 51 1/2"
Rough Opening 25 21/64" X 52"
Cashmere Clad Sash Exterior
Primed Pine Sash Interior
IG - 3/4" - 1 Lite
Low E2 w/Argon
Black Perimeter Bar
Ogee Interior Glazing Profile
Standard Bottom Rail
Beige Weather Strip
Solid Wood Covers

Unit: A3


Nailing Fin

Ultimate Casement - Right Hand Basic Frame 24 21/64" X 51 1/2" Rough Opening 25 21/64" X 52" Cashmere Clad Sash Exterior Primed Pine Sash Interior IG - 3/4" - 1 Lite Low E2 w/Argon Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Satin Taupe Folding Handle Satin Taupe Multi - Point Lock Aluminum Screen Satin Taupe Surround **Bright View Mesh** Standard Mull Charge 5 1/4" Jambs

***Note: This configuration meets a minimum structural performance of DP 20 through either physical testing or calculations in accordance with AAMA 450 and building code requirements. Mull certification ratings may vary from individual unit certification ratings. Reference the mulling chapter of the ADM for additional information.

***Note: Unit Availability and Price is Subject to Change

Line #3 Mark Unit: Net Price: Ext. Net Price: USD



As Viewed From The Exterior

Entered As: RO MO 99 1/2" X 52 3/4" Cashmere Clad Exterior Primed Pine Interior 4W1H - Rectangle Assembly Assembly Rough Opening 100" X 53"

Unit: A1

Ultimate Casement - Left Hand
Basic Frame 24 3/4" X 52 1/2"
Rough Opening 25 3/4" X 53"
Cashmere Clad Sash Exterior
Primed Pine Sash Interior
IG - 3/4" - 1 Lite
Low E2 w/Argon

Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Satin Taupe Folding Handle Satin Taupe Multi - Point Lock Aluminum Screen Satin Taupe Surround **Bright View Mesh** Unit: A2 Ultimate Casement - Stationary Basic Frame 24 3/4" X 52 1/2" Rough Opening 25 3/4" X 53" Cashmere Clad Sash Exterior Primed Pine Sash Interior IG - 3/4" - 1 Lite Low E2 w/Argon Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Solid Wood Covers Unit: A3 Ultimate Casement - Stationary Basic Frame 24 3/4" X 52 1/2" Rough Opening 25 3/4" X 53" Cashmere Clad Sash Exterior Primed Pine Sash Interior IG - 3/4" - 1 Lite Low E2 w/Argon Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Solid Wood Covers Unit: A4 Ultimate Casement - Right Hand Basic Frame 24 3/4" X 52 1/2" Rough Opening 25 3/4" X 53" Cashmere Clad Sash Exterior Primed Pine Sash Interior IG - 3/4" - 1 Lite Low E2 w/Argon Black Perimeter Bar Ogee Interior Glazing Profile Standard Bottom Rail Beige Weather Strip Satin Taupe Folding Handle Satin Taupe Multi - Point Lock Aluminum Screen Satin Taupe Surround **Bright View Mesh** Standard Mull Charge 5 1/4" Jambs Nailing Fin ***Note: This configuration meets a minimum structural performance of DP 20 through either physical testing or calculations in accordance with AAMA 450 and building code requirements. Mull certification ratings may vary from individual unit certification ratings. Reference the mulling chapter of the ADM for additional information. ***Note: Unit Availability and Price is Subject to Change