

DAVINCI SLATE

MULTI-WIDTH SLATE

Widths - 12", 10", 9", 7", 6"	Length - 18"	Thickness at Butt - 1/2"	Thickness at Tip - 1/8"
-------------------------------	--------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	6:12 or greater	8"	28	6.4	266 lbs	359/SQ
Straight	6:12 or greater	7.5"	28	6.8	283 lbs	381/SQ
Staggered	6:12 or greater	7"	28	7.3	304 lbs	409/SQ
Straight/Staggered	less than 6:12	6"	28	8.5	354 lbs	476/SQ

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Straight coursing may be used at any exposure up to 8.0" and staggered coursing may be used at any exposure up to 7.0"

HIP • RIDGE • STARTER • ACCESSORY

	6" Hip & Ridge	7" Hip & Ridge	One-Piece Hip & Ridge	12" Starter	12" Solid Accessory Tile
Pieces / Bundle	20	20	10	20	10
Linear Ft / Bundle	5*	5*	10	20	10
Pieces / Linear Ft	4*	4*	1	1	1
Nails Required	40/BDL	40/BDL	20/BDL	40/BDL	20/BDL

* At recommended 6" exposure Note: 9" pieces available for ridge; 4" pieces available for turrets.

SINGLE-WIDTH SLATE

Widths - 12"	Length - 18"	Thickness at Butt - 1/2"	Thickness at Tip - 1/8"
--------------	--------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	6:12 or greater	8"	22	6.6	275 lbs	291/SQ
Straight	6:12 or greater	7.5"	22	7.1	294 lbs	313/SQ
Staggered	6:12 or greater	7"	22	7.6	315 lbs	335/SQ
Straight/Staggered	less than 6:12	6"	22	8.8	367 lbs	388/SQ

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Straight coursing may be used at any exposure up to 8.0" and staggered coursing may be used at any exposure up to 7.0"

HIP • RIDGE • STARTER • ACCESSORY

	6" Hip & Ridge	7" Hip & Ridge	One-Piece Hip & Ridge	12" Starter	12" Solid Accessory Tile
Pieces / Bundle	20	20	10	20	10
Linear Ft / Bundle	5*	5*	10	20	10
Pieces / Linear Ft	4*	4*	1	1	1
Nails Required	40/BDL	40/BDL	20/BDL	40/BDL	20/BDL

* At recommended 6" exposure Note: 9" pieces available for ridge; 4" pieces available for turrets.

BELLAFORTÉ SLATE

Widths - 12"	Length - 15.5"	Thickness at Butt - 1/2"	Thickness at Tip - 3/8"
--------------	----------------	--------------------------	-------------------------

FIELD SHINGLES PER ROOFING SQUARE

Coursing	Roof Pitch	Max. Exposure	Pieces / Bundle	Bundles / Square	Weight / Square	Nails Required
Straight	4:12 or greater	12"	10	10	160 lbs	200/SQ

HIP • RIDGE • STARTER • ACCESSORY

	One-Piece Hip & Ridge	Rake	Starter	Transition Piece
Pieces / Bundle	10	20	20	10
Linear Ft / Bundle	10	20	20	10
Pieces / Linear Ft	1	1	1	1
Nails Required	20/BDL	40/BDL	40/BDL	30/BDL

TESTING & BUILDING CODE APPROVALS

Class A Fire; Class 4 Impact; Certified to 110MPH
 ICC-ES ESR-2119; Miami-Dade County, FL; CA Title 24; Texas Dept. of Insurance; LEED contribution; CCMC 14094-R

* Go to www.davinciroofscapes.com for the most up-to-date technical information.