APPLICABLE CODES

2015 INTERNATIONAL BUILDING CODE 2015 INTERNATIONAL FIRE CODE 2015 INTERNATIONAL MECHANICAL CODE 2017 NATIONAL ELECTRIC CODE 2015 UNIFORM PLUMBING CODE 2015 INTERNATIONAL ENERGY CONSERVATION CODE 2013 OR MOST RECENT ACCESSIBILITY GUIDELINES ICC/ANSI A117.1

GENERAL INFORMATION

USE AND OCCUPANCY: ASSEMBLY [A-2] : BANQUET HALL CONSTRUCTION TYPE: TYPE VB - UNPROTECTED [SPRINKLERED]

FIRE-RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS [HOURS] HOURLY RATINGS

	HOURLY RATINGS PRIMARY STRUCTUR	AI FRAME	0 HOURS		
			UNOUNS		
	BEARING WALLS EXTERIOR INTERIOR		0 HOURS 0 HOURS		
	NON BEARING WALLS EXTERIOR INTERIOR		0 HOURS 0 HOURS		
	FLOOR CONSTRUCTION	ON	0 HOURS		
	ROOF CONSTRUCTIO	N	0 HOURS		
	AREA ALLOWED PER FLOOR [TABLE 506.2] MAXIMUM: 18,000 S.F. PROVIDED: 2,539 S.F. ASSEMBI <u>1,446 S.F. UTILITY</u> TOTAL: 3,985 S.F. BUILDING HEIGHT: [TABLE 504.3]	-			
	MAXIMUM: 60'-0" PROVIDED: 38'-6"				
	NUMBER OF STORIES [TABLE 504.4] MAXIMUM: 2 PROVIDED: 2				
	NUMBER OF EXITS: REQUIRED: 2 PROVIDED: 4				
REQUIRED SEPARATION OF OCCUPANCIES [TABLE 508.4] NONE REQUIRED					
	MAXIMUM FLOOR AREA ALLOWANCES PER OCCUPANT [TABLE 1004.1.2] ASSEMBLY FLOOR AREAS [UNCONCENTRATED]: 2,539 S.F. / 15 S.F. NET = 169.2 [170] OCCUPANTS				
	UTILITY FLOOR AREAS:				
	<u>1,446 S.F. / 300 S.F. GF</u> TOTAL OCCUPANTS ALLOWED	ROSS	= 4.82 [5] OCCUPANTS = 175 OCCUPANTS		
	EGRESS WIDTH REQUIRED/PROVIDED 175 x 0.2" = 35"/140"		STAIR WIDTH REQUIRED/PROVID NOT APPLICABLE	ED	
	COMMON PATH OF EGRESS TRAVEL [TABL MAXIMUM: ACTUAL:	E 1006.2.1] 75'-0" 45'-10"			
	EXIT TRAVEL DISTANCE [TABLE 1017.2] MAXIMUM: ACTUAL:	250'-0" 98'-5"			
	SANITARY FIXTURE COUNTS [TABLE 2902.1	1]:			
		REQUIRED	[ASSEMBLY] T	ΓΟΤΑ	
	MEN LAVATORY WATER CLOSET URINAL		1 2 -		

WOMEN LAVATORY WATER CLOSET OTHER SERVICE SINK DRINKING FOUNTAIN

NOTES DRINKING WATER WILL BE PROVIDED DURING EVENTS







