

Certificate of Appropriateness

LIVING WITH HISTORY

Milwaukee Historic Preservation Commission/809 N. Broadway/PO Box 324/Milwaukee, WI 53201-0324/414-286-5712

Property
Description of work
Date issued

127 E. RESERVOIR AV.

k Install new back deck 4/10/2010

PTS ID 65054 COA, new back deck

conditions apply to this certificate of appropriateness: issued a certificate of appropriateness for the work listed above. The work was found to be consistent with preservation guidelines. The following In accordance with the provisions of Section 308-81(9) of the Milwaukee Code of Ordinances, the Milwaukee Historic Preservation Commission has

All work to be done according to attached drawings. Deck and railings will be painted upon completion

any changes or additions to this certificate before work begins. Work that is not completed in accordance with this certificate may be subject to correction orders or citations. If you require technical assistance, please contact Paul Jakubovich of the Historic Preservation staff as follows: Phone All work must be done in a craftsman-like manner, and must be completed within one year of the date this certificate was issued. Staff must approve (414) 286-5712 Fax: (414) 286-0232 E-mail: pjakub@milwaukee.gov.

requirements, please consult the Development Center's web site, www.mkedcd.org/build, or calt (414) 286-8210 or 821 If permits are required, you are responsible for obtaining them from the Milwaukee Development Center, If you have questions about permit


Paul Jakubovich

City of Milwaukee Historic Preservation

Copies to: Development Center, Ald. Milele Coggs, Inspector Bill Richter (286-2518)

Balusters





Se le ctions alusta

2 x2 baluster Most Styles 1855-1940

1855-1875 Italianate

Italianate/

Victorian Gothic

sawn baluster

1855-1885

board

THE PROPERTY OF THE PROPERTY O

Porches




Traditional Porch Floors

Porch floors should be constructed of center matched or tongue-and-groove wooden flooring, which typically measures 2-1/4" wide by 3/4" thick. This flooring gives the porch a fine finished appearance. The joists, which are the structural framing members to which the flooring is attached, should always be run parallel to the house so that the floor boards can be installed perpendicular to the house. The porch floor should also be very slightly pitched away from the house. This method of construction for a porch floor will shed water and make the porch last longer.

Some 11 920 between bosons

Joists parallel to the house


Center match or tongue-and-groove flooring



Porches



Basic Railing and Newel Post Design




the Historic Preservation Commission for most homes designs are appropriate for many houses built before 1940 and would be approved by The number of historic handrall and newel post designs is literally endless. The above


orches




Porch Skirting Designs




Rectangular Lattice, All Styles, 1855-1935



Sawn Skirting Boards, All Styles, 1865-1900



Cut-Out Panels, All Styles, 1875-1900



Handrail Design Tips For Porch Staircases A modern metal ralling on a wooden porch is gener compatible with the architecture of an older house : Jan-Alyan.

Porches